



C-9404

Conventional Sounder, Multi Tone, Shallow Base

General

The C-9404 conventional sounder is an audible fire alarm device. It gives an audible alarm signal when 24 VDC is applied to its inputs.



Details

- High sound output
- 2 Tones user selectable
- Shallow mounting base with optional deep base
- Wiring directly to base for easy installation
- LPCB Marked

C-9404

Conventional Sounder, Multi Tone, Shallow Base

Technical specifications

General

Compatibility	GST conventional systems
---------------	--------------------------

Electrical

Power supply type	24 VDC
Operating voltage	20 to 28 VDC (24 VDC typical)
Current consumption	≤ 35 mA

Sounder

Output level	≥ 95 dB @ 1 m Continuous
Frequency	Selectable
Selectable tones	2

Physical

Physical dimensions	110 x 95.9 mm (Ø x H)
Shipping weight	327.2 g
Colour	Red
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Shallow
Cable size	> 1.5 mm ²
Material	ABS

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	95% non-condensing
Environment	Indoor
IP rating	IP33C

Regulatory

Compliance	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-3



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit za.firesecurityproducts.com online or contact your sales representative.

Last updated on 19 May 2022 - 17:27